

# HD 32



## Naxpro-Truss HD 32 Truss System

Truss system in 2-point heavy duty design, especially suitable for exhibition stand and store construction, event technology, as well as a load bearing system for lighting systems. Through the use of compact format and high-load bearing capacity this system is equally well used for simple exhibition stands and highly complex rigging structures.

Through the use of cone connectors, the system is connected actuated by adherence. The connectors are included in delivery. To connect the truss all you need in terms of tools is a small aluminium hammer. Special design constructions and powder-coating are feasible in little time.



Load chart vertical

Span (m)	Distributed load	Deflection	Central single load	Deflection
m	kg/m	mm	kg	mm
1,0	1142,2	0,2	1142,2	0,3
2,0	569,5	1,3	1138,9	2,1
3,0	378,6	4,3	1135,7	6,9
4,0	283,1	10,3	849,0	12,3
5,0	225,9	20,1	676,3	19,3
6,0	186,9	34,6	560,6	27,8
7,0	136,4	47,2	477,6	38,0
8,0	103,7	61,7	414,9	49,7
9,0	81,3	78,1	365,7	63,2
10,0	65,2	96,5	326,1	78,2
11,0	53,3	116,9	293,4	95,0
12,0	44,3	139,3	265,9	113,5
13,0	37,3	163,7	242,3	133,8
14,0	31,7	190,2	221,9	156,0
15,0	27,2	218,6	204,0	180,0
16,0	23,5	249,1	188,2	205,9
19,0	15,7	353,2	149,6	295,6
20,0	13,9	392,1	139,0	329,7

High uniformly distributed loads are to be understood ideally distributed. The load application has to be made in the knot. The upper main pipe must be held sideways min. every 113,23 cm! The load values are calculated using 10.9 bolts.

Errors and alteration excepted



**Specifications**

Width: 290 mm  
 Tube: 50 x 3 mm  
 Braces: 20 x 2 mm  
 Alloy: EN-AW 6082 T6

**Incl. connecting set**

